

PRODUCT-DETAILS

# SBR-F-10.0.1-83

## SBR-F-10.0.1-83 RTC, 10gang, silver



### General Information

Extended Product Type	SBR-F-10.0.1-83
Product ID	2CKA006220A0859
EAN	4011395314500
Catalog Description	SBR-F-10.0.1-83 RTC, 10gang, silver
Long Description	Control element with room temperature controller function. For controlling commercially available actuating drives in combination with free@home Heating-/Fan-Coil Actuators. With display of set-value and current temperature. For transmitting switching, push-button, dimming and blind commands to an ABB-free@home® actuator. With integrated bus coupler. With labelling field. Number of bus subscribers: 1

### Installation

Instructions and Manuals	2CKA000073B5345
--------------------------	-----------------

### Technical

Number of LEDs	1
Compatible Bus Systems	free@home (TP)
Product Range	free@home
Mounting Type	Flush Mounted
Surface Finishing	Surface protection: Lacquered Surface finishing: Matt
Material	Plastic

RAL Number	RAL 9006 - White Aluminium
Color	aluminium silver
Number of Batteries	0
Application Function	Blind / Shutter / Shading Control Electrical Load and Light Control Room Climate Control

---

## Environmental

Ambient Air Temperature	Operation -5 ... +45 °C
Degree of Protection	IP20
RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	2CKA100000E4679
REACH Declaration	2CKA309999E9999
Temperature Class Default	I
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

---

## Dimensions

Product Net Width	90.1 mm
Product Net Height	167.1 mm
Product Net Depth / Length	44.2 mm
Product Net Weight	163 g
Built-In Depth (t <sub>2</sub> )	30.7 mm

---

## Classifications

ETIM 8	EC001101 - Room temperature controller for bus system
ETIM 9	EC001101 - Room temperature controller for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	9032 10 20
eClass	V11.0 : 27143133

---

## Categories

Low Voltage Products and Systems → Building and Home Automation Solutions → free@home → User Operation → ABB-Tenton® → 10 fold, RTC

