

PRODUCT-DETAILS

## N2180.4 BL

## DND/MUR corridor with LED not exchangeable White - Zenit



N2180.4 BL
2CLA218040N1101
8427238093833
DND/MUR corridor with LED not exchangeable White - Zenit
Color: White. Rated voltage: 127-230 Vac / 50-60 Hz Lamp: white LED Luminous flux: > 2 lumen at 1 meter Red diffuser Do Not Disturb (DND) symbol To be controlled with N2244.5 DND/MUR 2-gang interlocked switch Size: 1 module.

## Installation Instructions and 2CLX210109N1001 Manuals

Technical	
Data Sheet, Technical	9AKK10103A5108
Information	

N2180.4 BL 2

Rated Voltage (U <sub>r</sub> )	230 V
Design Range	Zenit
Lamp Type	LED not exchangeable
Mounting Type	Flush Mounted
Type of Fastening	Engage (Snap)
Surface Finishing	Untreated Glossy
Material	Plastic Thermoplastic
RAL Number	RAL 9010 - Pure White
Color	White
Lamp Color	White
Number of Batteries	0

Environmental	
Ambient Air Temperature	Operation -5 +35 °C Storage -5 +50 °C
Degree of Protection	IP20
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	2CLC218040N1101
REACH Declaration	9AKK108467A7464
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions	
Product Net Width	22 mm
Product Net Height	44 mm
Product Net Weight	0.027 kg
Built-In Depth (t <sub>2</sub> )	40 mm

2CLA218040N1102
2CLA218040N1103

Certificates and Declarations		
Declaration of	9AKK106930A5902	
Conformity - CE		

Classifications	
ETIM 8	EC000064 - Information light signal for domestic switching devices
ETIM 9	EC000064 - Information light signal for domestic switching devices
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85389099
UNSPSC	39121534

N2180.4 BL 3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Cover\ Plates\ and\ Control\ Elements \rightarrow Electronic\ Controls$ 





