

PRODUCT-DETAILS

8161 Switch Relay 230 V



General Information	
Extended Product Type	8161
Product ID	2CLA816100A1001
EAN	8427238016818
Catalog Description	Switch Relay 230 V
Long Description	Rated voltage: 230 V~, +10 % / -10 % Rated frequency: 50 Hz - 60 Hz 3 wire connection (neutral conductor required). For timer control element 8165.31 or 8165.3 Operation also possible via conventional push buttons 8104.X. Outputs: 1 Normally open contact, potential-bound Suitable for: 230 V incandescent lamps, 230 V halogen lamps, fluorescent lamps and low-voltage halogen lamps, that are operated via transformers. Rated current: 10 AX Rated power: 2300 W/VA Temperature range (Device): -25 °C to 55 °C Included: fixing claws

Installation		
Instructions and		

Manuals

© 2024 ABB. All rights reserved.

2024/01/31

Subject to change without notice

No document needed

Technical	
Data Sheet, Technical Information	9AKK107046A0356
Rated Voltage (Ur)	230 \
Rated Current (In)	10 4
Frequency (f)	5050 Hz
Minimum Switching	23002300 W
Capacity	
Design Range	Platform 8100 Alba
	Sky Niesser
Load Type	Universa
Mounting Type	Flush Mounted
Type of Fastening	Mounting with Screw
Model Number	Relay
Color	No color
Number of Batteries	C
Application Function	Electrical Load and Light Control
Environmental	
Ambient Air	Operation -5 +35 °C
Temperature	Storage -5 +50 °C
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Dimensions Product Net Width	0.062 m
Product Net Height	0.073 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.14 kg
Ordering Replaced Product ID	2CL0816100
(OLD)	
Certificates and Declarations	
Declaration of	No declaration needed
Conformity - CE	
Classifications	
ETIM 8	EC001588 - Electronic switch
ETIM 9	EC001588 - Electronic switch
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85365080

UNSPSC © 2024 ABB. All rights reserved.

2024/01/31

Subject to change without notice

39122200

Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Wiring Accessories - Light Switch Ranges} \rightarrow \text{Flush Mounted Inserts} \rightarrow \text{Electronic Inserts}$









3605