

PRODUCT-DETAILS

# BT/A 1.1

## BT/A1.1 Keypad, black, SM



### Informations générales

|                              |  |
|------------------------------|--|
| Extension du type de produit | BT/A 1.1   |
| Code de produit              | 2CDG280001R0011  |
| EAN                          | 4016779925563  |
| Description courte           | BT/A1.1 Keypad, black, SM  |
| Description longue           | used to operate and display the information of the system states of the GM/A 8.1 KNX Security Panel. System messages are displayed on a four-line LCD display. The multifunction and special keys mean that all the system functions can be operated easily. Safety-relevant functions are protected by a user PIN. Fife Keypads can be connected to each Security Panel. There is no need for an external voltage supply, the keypads are supplied via the Keypad-Bus. The device can be used in systems with increased system requirements according to VdS Class A, B and C, DIN VDE 0833 Level 1, 2 and 3 and EN 50131/IEC 62642 Level 1, 2 and 3. |

### Installation

|                         |                 |
|-------------------------|-----------------|
| Instructions et manuels | 2CDG941141P0003 |
|-------------------------|-----------------|

### Technique

|  |                 |
|--|-----------------|
| Fiche produit, informations techniques | 2CDC513072D0203 |
| Auxiliary Voltage AC/DC                | 12 V DC         |

|                        |                 |
|------------------------|-----------------|
| Power Loss             | 0.9 W           |
| Compatible Bus Systems | S-Bus/XIB       |
| Type de montage        | Surface Mounted |
| Manual Operation       | Oui             |
| Couleur                | black           |
| Nombre de batteries    | 0               |
| Taille d'écran         | 4 in            |

## Environnement

|                      |                                   |
|----------------------|-----------------------------------|
| Indice de protection | IP30                              |
| Statut RoHS          | Following EU Directive 2011/65/EU |
| Informations RoHS    | 2CDK513061D2701                   |
| REACH Declaration    | 9AKK107492A1906                   |

## Dimensions

|                      |          |
|----------------------|----------|
| Produit Largeur Net  | 118 mm   |
| Produit Hauteur Net  | 237 mm   |
| Produit Longueur Net | 24.5 mm  |
| Poids net            | 0.325 kg |

## Certificats et Déclarations (Numéro de document)

|                                   |                 |
|-----------------------------------|-----------------|
| Déclaration de Conformité<br>- CE | 2CDK513061D2701 |
|-----------------------------------|-----------------|

## Classifications

|                                   |  |
|-----------------------------------|--|
| ETIM 8                            | EC001767 - Operating and display device for intrusion detection system |
| ETIM 9                            | EC001767 - Control and display device for danger detection system      |
| Catégorie DEEE                    | 5. Small Equipment (No External Dimension More Than 50 cm)             |
| WEEE B2C / B2B                    | Business To Consumer   |
| CN8                               | 8531 20 95   |
| eClass                            | V11.0 : 27390313   |
| Code de classification<br>d'objet | A  |

---

## Catégories

---

Produits basse tension → Home and Building Automation → Alarme intrusion → Alarm System - GMA → Keypads

Produits basse tension → Home and Building Automation → KNX → Security - Alarm System GMA → Keypads

