

PRODUCT-DETAILS

# 8531.2 PL

## Wireless switch transmitter - 2 channel - Silver 2 channel Radio Control Silver - Sky Niessen



### Informations générales

Extension du type de produit	8531.2 PL
Code de produit	2CLA853120A1301
EAN	8427238146072
Description courte	Wireless switch transmitter - 2 channel - Silver 2 channel Radio Control Silver - Sky Niessen

Description longue	<p>Color: Silver.                  2-gang wall-mounted transmitter independent of mains power supply.                  For switching and dimming.                  For controlling blinds and light scenes.                  2 radio channel can be operated or up to 2 light scenes can be called up.                  For wireless pill type actuators: 8130.4, 8130.5, 8130.7 &amp; 8130.6.                  Send frequency: 868 MHz.                  Free-field range: approx. 100 m.                  Power supply: lithium button cell battery Type CR2032.                  Battery service life: typically 5 years, therefore practically maintenance-free.                  Rated voltage: 3 Vdc.                  Automatic monitoring of battery life.                  Including fixing plate for mounting on smooth walls or on switch boxes.                  Control element: Switch contacts top/bottom.                  Display elements: LED to indicate the transmission.                  Temperature range (Device): -5 °C to 45 °C.                  Battery included in delivery.</p>
--------------------	--

### Installation

Instructions et manuels	2CLX850009A1001
-------------------------	-----------------

---

## Downloads Préférés

---

Marketing Video	9AKK106930A1594 9AKK108468A9590
-----------------	------------------------------------

---



---

## Technique

---

Fiche produit, informations techniques	9AKK107046A0356
Number of Channels	2
Design Range	Sky Niessen
Norme de transmission	Radio Control
Type de montage	Surface Mounted
Finition de surface	Decor Matt
Matériau	Plastic Thermoplastic
Couleur	Silver
Composition chimique de la batterie	Lithium
Type de batterie	Pile bouton
Poids de la batterie	0.01 kg
Nombre de batteries	1
Application Function	Electrical Load and Light Control

---



---

## Environnement

---

Température de l'air ambiant	Operation -5 ... +35 °C Storage -5 ... +50 °C
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CLC853120A1301
REACH Declaration	9AKK108467A7464
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

---



---

## Dimensions

---

Produit Largeur Net	0.054 m
Produit Hauteur Net	0.054 m

---



---

## Certificats et Déclarations (Numéro de document)

---

Déclaration de Conformité - CE	No declaration needed
--------------------------------	-----------------------

---



---

## Classifications

---

ETIM 8	EC000257 - Transmitter/Remote control for domestic switching devices
ETIM 9	EC000257 - Transmitter/Remote control for domestic switching devices

Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85389099
UNSPSC	39121704

---

## Catégories

---

Produits basse tension → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Electronic Controls

