

PRODUCT-DETAILS

6131/50-24-500

6131/50-24-500 KNX Presence Cor. W



Informazioni generali

Tipo	6131/50-24-500
ID prodotto	2CKA006132A0399
EAN	4011395216446
Descrizione catalogo	6131/50-24-500 KNX Presence Cor. W

Descrizione	<p>Detection range: rectangular. For mounting height of 3 m: frontal toward the detector at a max. of 20 m x 3 m (at a max. of 10 m x 3 m per side). Crosswise toward the detector at a max. of 30 m x 3 m (max. of 15 m x 3m per side). With integrated KNX bus coupler.</p> <p>Mounting height 27 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Regulation in response to the movement possible. Using the device as presence and/or movement detectors. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. Ceiling mounting on suspended ceilings with spring clamps, on solid ceilings in surface-mounting boxes 6131/39-xxx(-500) or on VDE flush-mounted boxes with intermediate ring for VDE flush-mounted boxes 6131/38-xxx(-500). Suitable for false ceilings with a board thickness from 9 to 25 mm.</p> <p>Hole size: Ø 68 mm. Cannot be installed in British Standard or VDE flushmounted box.</p> <p>Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.</p>
-------------	---

Installation

Istruzioni e manuali	No document needed
----------------------	--------------------

Circular Value

Circular Design Principles Lifetime	2CKA000073B5454
Group Waste to Landfill Target	No non-hazardous waste is sent to a landfill
Sustainable Material Content in Packaging	FSC Recycled Paperboard - 90 %
Improved Resource Efficiency for Customers	Digital Efficiency - Product is digitally-supported to optimize usage and eventually optimize customer asset
Offered with Extended Lifetime	Product Upgradability
Offered with Takeback Services	Take Back for Recycling

Eco Transparency

Dichiarazione prodotto ambientale - EPD	9AKK108468A1033
--	-----------------

Dati tecnici

Scheda tecnica	2CKA006132D0202
Numero di canali	2
Sistemi bus compatibili	KNX (TP)
Gamma prodotto	KNX
Minimum Switching Time	Switch-On 10 secondo [unità di misura del tempo]
Tipo di montaggio	Surface Mounted Flush Mounted
Finitura superficie	Surface protection: Untreated Surface finishing: Matt
Materiale	Thermoplastic
Posizione di montaggio	Ceiling
Model Number	Presence detector
RAL Number	RAL 9016 - Bianco traffico
Colore	studio white matt
Number of Batteries	0
Application Function	Electrical Load and Light Control

Dati ambientali

Temperatura ambiente	In funzione -5 ... +45 °C
Grado di protezione	IP20
Dichiarazione RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informazioni RoHS	2CKA200000E4559
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensioni

Larghezza prodotto	91 mm
Altezza prodotto	91 mm
Profondità prodotto	49 mm
Peso netto prodotto	102 g
Profondità integrata (t ₂)	22 mm

Ordinazione

ID prodotto sostituito
(VECCHIO)

6132-0-0399

Certificati e dichiarazioni (numero del documento)

Dichiarazione di
conformità - CE

2CKA100000E1102

Classificazioni

ETIM 8	EC001582 - Movement sensor for bus system
ETIM 9	EC001582 - Movement sensor for bus system
Categoria RAEE	5. Piccole apparecchiature (nessuna dimensione esterna superiore a 50 cm)
CN8	Business To Consumer
Tipo di oggetto design	8536 50 80
eClass	V11.0 : 27143144

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006132A0403	6131/38-24-500 Intermediate ring fm box W	6131/38-24-500	1	pezzo (i)
2CKA006899A2304	Protection Cover	6898	1	pezzo (i)

Categorie

Prodotti di bassa tensione → Automazione case ed edifici → KNX → Presence Detection → Presence Detectors

