

PRODUCT-DETAILS

TB/U6.4.1-CG

TB/U6.4.1-CG Control element 6g.



Informazioni generali

| | |
|----------------------|----------------------------------|
| Tipo | TB/U6.4.1-CG |
| ID prodotto | 2CKA006300A1542 |
| EAN | 4011395230763 |
| Descrizione catalogo | TB/U6.4.1-CG Control element 6g. |

Descrizione

Ordering possible only in connection with the design ID. The icons and/or texts are configured by means of a web configuration tool. Freely configurable multifunction control element. With integrated KNX bus coupler. With integrated temperature sensor. With integrated proximity function. Push switch function: switching / dimming / blind / sending values / scenes etc. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. The bus connection is provided via the enclosed bus terminal. Number of bus subscribers: 1

Installation

| | |
|----------------------|--------------------|
| Istruzioni e manuali | No document needed |
|----------------------|--------------------|

Dati tecnici

| | |
|----------------------------|--------------------|
| Scheda tecnica | No document needed |
| Numero di pulsanti | 6 |
| Number of Actuation Points | 6 |

| | |
|-------------------------|--|
| Sistemi bus compatibili | KNX (TP) |
| Gamma prodotto | KNX |
| Design Range | tacteo |
| Tipo di montaggio | Surface Mounted |
| Finitura superficte | Surface protection: Untreated Surface finishing: Glossy |
| Materiale | Glass |
| Colore | other |
| Number of Batteries | 0 |
| Application Function | Blind / Shutter / Shading Control Electrical Load and Light Control Room Climate Control |

Dati ambientali

| | |
|---|--|
| Temperatura ambiente | In funzione -5 ... +45 °C |
| Grado di protezione | IP20 |
| Dichiarazione RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informazioni RoHS | 2CKA200000E5454 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensioni

| | |
|--|---------|
| Larghezza prodotto | 86 mm |
| Altezza prodotto | 86 mm |
| Profondità prodotto | 34 mm |
| Peso netto prodotto | 104.5 g |
| Profondità integrata (t ₂) | 35 mm |

Certificati e dichiarazioni (numero del documento)

| | |
|----------------------------------|-----------------|
| Dichiarazione di conformità - CE | 2CKA100000E2527 |
|----------------------------------|-----------------|

Classificazioni

| | |
|------------------------|---|
| ETIM 8 | EC000672 - Touch sensor for bus system |
| ETIM 9 | EC000672 - Touch sensor for bus system |
| Categoria RAEE | 5. Piccole apparecchiature (nessuna dimensione esterna superiore a 50 cm) |
| CN8 | Business To Consumer |
| Tipo di oggetto design | 8536 50 80 |
| eClass | V11.0 : 27143138 |

Categorie

Prodotti di bassa tensione → Automazione case ed edifici → KNX → User Operation → ABB tacteo® → 6 fold



360°