

PRODUCT-DETAILS

6586-500

6586-500Dimmer, MW:1



Informazioni generali

Tipo	6586-500
ID prodotto	2CKA006590A0191
EAN	4011395208519
Descrizione catalogo	6586-500Dimmer, MW:1

Descrizione	<p>Touch dimmer with local operation. Optimised for dimming of retrofit LED lamps (LEDi). For dimmable Retrofit-LEDs (LEDi). For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers. For incandescent lamps, 230V tungsten halogen lamps and low-voltage halogen lamps with conventional transformers or electronic transformers and dimmable halogen energy-saving lamps. Mix operation of LEDi with conventional loads possible. With the following functions: memory, snooze, wake-up, children's room, central off, cleaning light and time function. For staircase lighting control with automatic switch-off and warning function according to DIN 18015-2. Supports the adherence to the energy saving ordinance (EnEV 2014). Low-noise level by MOSFET transistors. With electronic short-circuit protection. With electronic overload protection. With manually adjustable operating mode: trailing / leading edge control. With adjustable minimum/maximum brightness. With light value storage. Operation also possible via conventional push buttons (2020 US, 2021/6 UK). Extension unit input for short switching pulses (push-button) and continuous contact (switch/timer). Extension unit input designed as wide voltage input (8-230 V AC/DC) galvanic isolation. Nominal power: 2 - 100 W/VA (retrofit LED loads). Nominal power: 10 - 200 W/VA (non-LED loads). Rated frequency: 50 Hz/60 Hz</p>
-------------	--

Installation

Istruzioni e manuali	DEBJE-6590-0-0191
----------------------	-------------------

Dati tecnici

Scheda tecnica	No document needed
Applicazione	Dimmable Retrofit-LEDs (LEDi)
Tensione nominale (U _r)	230 V
Tensione nominale di alimentazione di controllo (U _s)	8...230 V
Tensione ausiliaria AC/DC	230 V AC/DC
Frequenza (f)	50...60 Hz
Frequenza nominale (f)	50 ... 60 Hz
Perdita di potenza	0.5 W
Power Watt	2...100 V·A
Tipo di attuatore	Push button
Tipo di connessione	Screw Clamp
Tipo di carico	Universal and LED Retrofit
Tipo di montaggio	DIN-Rail
Type of Fastening	Snapper Mounting
Finitura superficie	Surface protection: Untreated Surface finishing: Matt
Materiale	Thermoplastic
RAL Number	RAL 7035 - Grigio luce
Colore	grey
Application Function	Electrical Load and Light Control
Tensione alimentazione di controllo	8...230 V

Dati ambientali

Temperatura ambiente	In funzione 0 ... +35 °C
Dichiarazione RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informazioni RoHS	2CKA200000E5976
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensioni

Larghezza in numero di intervalli modulari	1
Larghezza prodotto	65 mm
Altezza prodotto	74 mm
Profondità prodotto	18 mm
Peso netto prodotto	56 g

Ordinazione

ID prodotto sostituito (VECCHIO)	6590-0-0191
----------------------------------	-------------

Certificati e dichiarazioni (numero del documento)

Dichiarazione di conformità - CE	2CKA100000E1708
----------------------------------	-----------------

Classificazioni

ETIM 8	EC000025 - Dimmer
ETIM 9	EC000025 - Dimmer
Categoria RAEE	5. Piccole apparecchiature (nessuna dimensione esterna superiore a 50 cm)
CN8	Business To Consumer
Tipo di oggetto design	8536 50 80
eClass	V11.0 : 27144014

Categorie

Prodotti di bassa tensione → Apparecchi modulari → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights

Prodotti di bassa tensione → Wiring Accessories - StandAlone Electronics → Other Stand Alone Electronics → Other Stand Alone Electronics

