

PRODUCT-DETAILS

6819/51-24-500

Presence Detector 30 m 2300 W



Informazioni generali

Tipo	6819/51-24-500
ID prodotto	2CKA006800A2745
EAN	4011395217672
Descrizione catalogo	Presence Detector 30 m 2300 W

Descrizione	<p>Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. With power relays for LED operation. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 30 m x 3 m, frontal 20 m x 3 m. Extension of the detection range by means of master/slave combination. Mounting height 27 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor). With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 92 sectors with 368 switching segments Individual deactivation and adjustment of sensitivity of individual sensors possible. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. With selectable dynamic switch-off delay. Suitable for false ceilings with a board thickness from 9 to 25 mm.</p>
-------------	--

Dati tecnici

Scheda tecnica	2CKA001673B9577
Funzione	Setting Options by Bluetooth
Tensione nominale (U _r)	230 V AC
Tensione ausiliaria AC/DC	110 V AC/DC 230 V AC/DC
Tipo di tensione d'ingresso	AC
Range di corrente	Maximum 800 A
Frequenza (f)	50...60 Hz
Frequenza nominale (f)	50 / 60 Hz
Potenza massima di commutazione	2300 W
Perdita di potenza	0.3 W
Intervallo di misura	30 m
Numero di uscite	1
Number of Switching Zones	368
Tempo di ritardo (T)	Off 0 secondo [unità di misura del tempo] On 0 secondo [unità di misura del tempo]
Minimum Switching Time	Switch-On 60 secondo [unità di misura del tempo]
Tipo di connessione	Plug Clamp
Tipo di carico	230 V incandescent lamps
Tipo di montaggio	Built-in
Tipo sensore	Passive infrared
Finitura superficie	Surface protection: Untreated Surface finishing: Matt
Materiale	Plastic Thermoplastic
Posizione di montaggio	Ceiling
Illuminamento	5 ... 2000 lx
Model Number	Presence detector
RAL Number	RAL 9016 - Bianco traffico
Colore	studio white matt
Application Function	Electrical Load and Light Control

Dati ambientali

Temperatura ambiente	In funzione -5 ... +45 °C
Grado di protezione	IP40
Dichiarazione RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informazioni RoHS	2CKA200000E6492
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensioni

Larghezza prodotto	94 mm
Altezza prodotto	94 mm
Profondità prodotto	76 mm
Peso netto prodotto	170.4 g
Profondità integrata (t ₂)	49 mm

Certificati e dichiarazioni (numero del documento)

Dichiarazione di
conformità - CE

2CKA200000E6492

Classificazioni

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Categoria RAEE	5. Piccole apparecchiature (nessuna dimensione esterna superiore a 50 cm)
CN8	Business To Consumer
Tipo di oggetto design	8536 50 80
eClass	V11.0 : 27144007

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A2801	Presence Detector	6889/50-24-500	1	pezzo (i)
2CKA006499A0002	Extension Module	6494-500	1	pezzo (i)
2CKA006899A2304	Protection Cover	6898	1	pezzo (i)

Categorie

Prodotti di bassa tensione → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

