

Touch panel monitor for FHV7 Smart Camera

Advantech PPC-3100S-OMR



* Additional software installation may be required depending on the software version of the smart camera.


Specifications

Model		PPC-3100S-OMR (Advantech)
LCD	Display Type	10.4" TFT LCD (LED backlight)
	Resolution	1024×768
	Luminance	350 cd/m ²
	Contrast Ratio	1200
	Backlight Lifetime	30,000 hr (min.)
	Touch Type	Capacitive
External Interface	Ethernet	10/100/1000 Mbps Ethernet × 2
	USB I/F	USB 2.0×1、USB 3.0×1
Power Consumption	Input Voltage	12 to 24 VDC
	Power Consumption	16 W
Environment	Ambient Temperature Range	Operating: 0 to 50°C Storage: −40 to 60°C
	Ambient Humidity Range	10% to 95% at 40°C (With no condensation)
	Vibration	Operating Random Vibration Test 5 to 500 Hz, 2 Grms, follow IEC 60068-2-64
	Shock	Operating 10 G peak acceleration (11 ms duration), follow IEC 60068-2-27
	EMC	CE, FCC Class B, BSMI
	Safety	CB, CCC, BSMI, UL
Dimensions		272×217×46 mm
Weight		1.9 kg
Front Panel Protection		IP65 compliant
Mounting		Panel mount, VESA mount, Wall mount
Accessories		Instruction sheet, Connector for power supply, Mounting screws and brackets for panel mount

Accessories (Sold Separately, Advantech)

Item	Model
ARM VESA Standard (A-CLEVER) for PPC Series	PPC-ARM-A03
Wall mount kit for PPC Series	PPC-174T-WL-MTE
Stand for PPC Series	PPC-Stand-A1E
ADP A/D 100-240V 90W 19V W/PFC	96PSA-A90W190T-1
Power cord 3P UL 10 A 125 V 1.8 m	1700001524
Power cord 3P Europe (WS-010+083) 1.83 m	170203183C
Power cord 3P/3P PSE 1.8 m	1700008921
Power cord 3P CCC (China) 1.8 m	96CB-POWER-B-1.8M

I/O View



A. Power switch

D. RS-232/422/485

B. DC-In

E. RJ45LAN × 2


C. RS-232

F. USB 2.0 x 1, USB 3.0 x 1


is used as an operator interface.

*The serial ports C and D are not used when the PPC-3100S-OMR

Dimensions



(Unit:mm)



Panel Cutout Dimensions: 265 x 210 mm

• Company names and product names in this document are the trademarks or registered trademarks of their respective companies.

Warranty

Ask Advantech about the warranty period and coverage of this product.

Contact about touch panel monitor

Find your local office on the Advantech website: https://www.advantech.com/contact/offices/

Recommended Industrial Touch Panel IPC/ Monitor

If you require a more industrial solution or larger screensizes, our FHV7 smart camera's work perfect with Omron's Industrial PC systems (e.g. NYP-series) Find your preferred Industrial PC systems at: http://www.ia.omron.com/products/family/3633/

Contact about smart camera

OMRON Corporation Industrial Automation Company

Kyoto, JAPAN

Contact: www.ia.omron.com

Regional Headquarters OMRON EUROPE B.V.

Wegalaan 67-69, 2132 JD Hoofddorp The Netherlands Tel: (31)2356-81-300/Fax: (31)2356-81-388

OMRON ASIA PACIFIC PTE. LTD.

No. 438A Alexandra Road # 05-05/08 (Lobby 2), Alexandra Technopark, Singapore 119967 Tel: (65) 6835-3011/Fax: (65) 6835-2711

OMRON ELECTRONICS LLC

2895 Greenspoint Parkway, Suite 200 Hoffman Estates, IL 60169 U.S.A. Tel: (1) 847-843-7900/Fax: (1) 847-843-7787

OMRON (CHINA) CO., LTD.

Room 2211, Bank of China Tower, 200 Yin Cheng Zhong Road, PuDong New Area, Shanghai, 200120, China Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

Authorized Distributor:

© OMRON Corporation 2019 All Rights Reserved. In the interest of product improvement, specifications are subject to change without notice.

Cat. No. Q268-E1-01

0319(0319)