## **Product Technical Sheet**

31 Aug 2021 08:02





## 204.CA22B-T2T2A PILLAR CA 2 SOCKETS WITH LOCK

Type 2 3P+N+E 32A 400V~ 22kW 63A 400V 3P+N+E IP54 IK10

**Product Approvals** 

| TECHDATA                |                                  | STANDARDS AND LAWS                      |   |
|-------------------------|----------------------------------|---|---|
| Type of product         | PILLAR CA 2 SOCKETS<br>WITH LOCK | IEC 61439-7 (2018)                      | switchgear and controlgear assemblies -<br>Part 7: Assemblies for specific                            |
| Commercial series       | LIBERA Series                    |   | applications such as marinas, camping<br>sites, market squares, electric vehicle<br>charging stations |
| Synthetical description | PILLAR CA 2 SOCKETS<br>WITH LOCK | EN IEC 61851-1<br>(2019)                | [European Standard] Electric vehicle conductive charging system - Part 1:                             |
| Material                | VARNISHED METAL                  | DIRECTIVE LOW<br>VOLTAGE 2014/35<br>/UE | General requirements<br>[European Directives] Low Voltage<br>Directive                                |
| EV standard             | Type 2 3P+N+E 32A 400V~<br>22kW  |   |   |
| Rated current           | 63A                              | DIRECTIVE EMC<br>2014/30/UE             | [European Directives] Electromagnetic<br>Compatibility Directive                                      |
| Rated voltage           | 400V                             |   |   |
| Working frequency       | 50/60Hz                          |   |   |
| Poles                   | 3P+N+E                           |   |   |
| Protection degree IP    | IP54                             |   |   |
| Working temperature     | -30°C/+50°C                      |   |   |
| Protection degree IK    | IK10                             |   |   |
| Colour                  | GREY                             |   |   |
| Mounting version        | ON TURRET                        |   |   |
| Dimensions              | 385x1510x263mm                   |   |   |