



## 204.CL22B-T23A

# PILLAR CL 2 SOCKETS WITH LOCK

Type 2 3P+N+E 32A 400V~ 22kW Type 3A  
1P+N+E 16A 230V~ 3,7kW 32A 400V 3P+N+E  
IP54 IK10

Product Approvals

| TECHDATA                |                                | STANDARDS AND LAWS                |  |
|-------------------------|--------------------------------|-----------------------------------|--|
| Type of product         | PILLAR CL 2 SOCKETS WITH LOCK  | IEC 61439-7 (2018)                | [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Commercial series       | LIBERA Series                  |                                   |  |
| Synthetical description | PILLAR CL 2 SOCKETS WITH LOCK  | EN IEC 61851-1 (2019)             | [European Standard] Electric vehicle conductive charging system - Part 1: General requirements   |
| Material                | VARNISHED METAL                | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive  |
| EV standard             | Type 2 3P+N+E 32A 400V~ 22kW   | DIRECTIVE EMC 2014/30/UE          | [European Directives] Electromagnetic Compatibility Directive  |
| EV standard             | Type 3A 1P+N+E 16A 230V~ 3,7kW |                                   |  |
| Rated current           | 32A                            |                                   |  |
| Rated voltage           | 400V                           |                                   |  |
| Working frequency       | 50/60Hz                        |                                   |  |
| Poles                   | 3P+N+E                         |                                   |  |
| Protection degree IP    | IP54                           |                                   |  |
| Working temperature     | -25°C/+40°C                    |                                   |  |
| Protection degree IK    | IK10                           |                                   |  |
| Colour                  | GREY                           |                                   |  |
| Mounting version        | ON TURRET                      |                                   |  |
| Dimensions              | 450x1670x470mm                 |                                   |  |