



204.UB21B-3CUN

CON. UNIT 2 SOCKET WITH LOCK

Type 3C 1P+N+E 16A 230V~ 3,7kW UNEL
 1P+N+E 16A 230V~ 3,7kW 32A 230V 1P+N+E
 IP54 IK07

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	CON. UNIT 2 SOCKET WITH LOCK	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Commercial series	LIBERA Series		
Synthetical description	CON. UNIT 2 SOCKET WITH LOCK	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Material	ENGINEERING PLASTIC	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 3C 1P+N+E 16A 230V~ 3,7kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
EV standard	UNEL 1P+N+E 16A 230V~ 3,7kW		
Rated current	32A		
Rated voltage	230V		
Working frequency	50/60Hz		
Poles	1P+N+E		
Protection degree IP	IP54		
Working temperature	-25°C/+40°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK07		
Colour	GREY		
Mounting version	SURFACE MOUNTING		