Product Technical Sheet

21 Feb 2022 17:04





245.M6398

SURFACE MOUNT. APPLIANCE INLET

63A 3P+N+E 6h 346-415V 50Hz 60Hz Screw terminals

Product Approvals

| TECHDATA | | STANDARDS | AND LAWS |
|----------------------------|-----------------------------------|--|--|
| Commercial series | OPTIMA Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Type of product | SURFACE MOUNT. APPLIANCE INLET | and couplers for industrial purposes. Page 2: Dimensional interchangeability requirements for pin and contact-tube | 1: General requirements [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Synthetical description | SURFACE MOUNT. APPLIANCE INLET | | |
| Mounting version | SURFACE MOUNTING | DIRECTIVE LOW [European Directives] Low Voltage VOLTAGE 2014/35 Directive | |
| Rated current | 63A | | |
| Poles | 3P+N+E | | |
| Hour position | 6h | | |
| Rated voltage (range) | 250-400V | | |
| Rated voltage | 346-415V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67/IP69 | | |
| Protection degree IK | IK08 | | |
| Types of available outlets | ANGLED | | |
| Terminals | Screw terminals | | |

| Contact material | CuZn (brass) | |
|----------------------------|---------------|--|
| Surface treatment contacts | Nickel-plated | |
| Cable entry | M32X1,5 | |