Product Technical Sheet

21 Feb 2022 17:09





246.6393

FLUSH MOUNTING APPLIANCE INLET

63A 2P+E 6h 200-250V 50Hz 60Hz 100X110MM Screw terminals

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Commercial series	OPTIMA Series	CEI EN 60309-1 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part
Type of product	FLUSH MOUNTING APPLIANCE INLET	1: General requirements CEI EN 60309-2 [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part	
Synthetical description	FLUSH MOUNTING APPLIANCE INLET		2: Dimensional interchangeability requirements for pin and contact-tube accessories
Mounting version	FLUSH MOUNTING	DIRECTIVE LOW [European Directives] Low Voltage VOLTAGE 2014/35 Directive	
Rated current	63A		
Poles	2P+E		
Hour position	6h		
Rated voltage (range)	200-250V		
Rated voltage	200-250V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	BLUE		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP66/IP67		
Protection degree IK	IK08		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Surface treatment contacts	Nickel-plated	
Flange	100X110MM	