## **Product Technical Sheet**

21 Feb 2022 16:52





## **415.6360** FLUSH-MOUNTING SOCKET

63A 2P+E 4h 100-130V 50Hz 60Hz 100X110MM Screw terminals

**Product Approvals** 

| TECHDATA                   |                           | STANDARDS  | S AND LAWS   |
|----------------------------|---------------------------|--|--|
| Type of product            | FLUSH-MOUNTING<br>SOCKET  | EN 60309-1 (1999)  | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements     |
| Commercial series          | OPTIMA Series             | and coupler<br>2: Dimensio<br>requirement  | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part                             |
| Synthetical description    | FLUSH-MOUNTING<br>SOCKET  |  | 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Mounting version           | FLUSH/SURFACE<br>MOUNTING | EN 60309-1/A1<br>(2007)  | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements     |
| Rated current              | 63A                       | EN 60309-2/A1 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |  |
| Poles                      | 2P+E                      |  | 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position              | 4h                        | DIRECTIVE LOW  | [European Directives] Low Voltage Directive  |
| Rated voltage (range)      | 50-200V                   |  |  |
| Rated voltage              | 100-130V                  |  |  |
| Working frequency          | 50Hz                      |  |  |
| Working frequency          | 60Hz                      |  |  |
| Colour                     | YELLOW                    |  |  |
| Material                   | THERMOPLASTIC             |  |  |
| Protection degree          | Watertight                |  |  |
| Protection degree IP       | IP66/IP67                 |  |  |
| Protection degree IK       | IK08                      |  |  |
| Types of available outlets | ANGLED                    |  |  |
|                            |                           |  |  |

| Terminals        | Screw terminals |
|------------------|-----------------|
| Contact material | CuZn (brass)    |
| Flange           | 100X110MM       |