Product Technical Sheet

21 Feb 2022 17:50





417.3264 FLUSH-MOUNTING SOCKET

32A 3P+E 9h 200-250V 50Hz 60Hz 84X106MM Screw terminals

Product Approvals

| TECHDATA | | STANDARDS | S AND LAWS |
|----------------------------|--------------------------|---|--|
| Type of product | FLUSH-MOUNTING SOCKET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | EUREKA Series | and couplers for industrial purposes. I 2: Dimensional interchangeability requirements for pin and contact-tube | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Synthetical description | FLUSH-MOUNTING SOCKET | | 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Mounting version | FLUSH MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 | [European Directives] Low Voltage Directive |
| Rated current | 32A | /UE | |
| Poles | 3P+E | | |
| Hour position | 9h | | |
| Rated voltage (range) | 200-250V | | |
| Rated voltage | 200-250V | | |
| Working frequency | 50Hz | | |
| Working frequency | 60Hz | | |
| Colour | BLUE | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK07 | | |
| Types of available outlets | ANGLED | | |
| Terminals | Screw terminals | | |

| Contact material | CuZn (brass) | |
|------------------|--------------|--|
| Flange | 84X106MM | |