Product Technical Sheet

21 Feb 2022 17:09





422.16664

FLUSH-MOUNTING SOCKET

16A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz 60Hz 75X75MM Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|--------------------------|--------------------|---|
| Commercial series | EUREKA Series | EN 60309-1 (1999) | and couplers for industrial purposes. Part |
| Type of product | FLUSH-MOUNTING SOCKET | EN 60309-2 (1999) | 1: General requirements [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations [European Directives] Low Voltage Directive |
| Synthetical description | FLUSH-MOUNTING SOCKET | | |
| Mounting version | FLUSH MOUNTING | | |
| Rated current | 16A | | |
| Poles | 3P+E | | |
| Hour position | 3h | | |
| Rated voltage (range) | 250-400V | | |
| Rated voltage | 380V 50Hz / 440V 60Hz | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP44 | | |
| Protection degree IK | IK09 | | |
| Types of available outlets | STRAIGHT | | |
| Terminals | Screw terminals | | |

| Contact material | CuZn (brass) | |
|------------------|--------------|--|
| Flange | 75X75MM | |