Product Technical Sheet

21 Feb 2022 17:36



546.1686

INTERLOCKED SOCKET

16A 3P+E 6h 380-415V 50Hz 60Hz Screw terminals With mechanical interlock

Product Approvals

TECHDATA

Commercial series	QUADRA Series
Type of product	INTERLOCKED SOCKET
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING
Rated current	16A
Poles	3P+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP67
Protection degree IK	IK07
Terminals	Screw terminals
Contact material	CuZn (brass)

STANDARDS AND LAWS

EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive

Cable entry	PG 21
Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER