



590.EL4012.SN

SWITCH DISCONNECTOR

40A 1P+SN IP66/IP69 110x150x87mm Y1 IK09
 GENERAL YELLOW/RED SN (SOLID
 NEUTRAL) LOCKABLE ON-OFF GW 650°C

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|---|
| Type of product | SWITCH DISCONNECTOR | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | ISOLATORS-TP Series | | |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | ENGINEERING PLASTIC | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Protection degree IP | IP66/IP69 | | |
| Type | GENERAL | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Colour | YELLOW/RED | | |
| Rated current | 40A | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Poles | 1P+SN | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Switch size | Y1 | | |
| Rated voltage | 250V | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Dimensions | 110x150x87mm | | |
| Notes | SN (SOLID NEUTRAL) | | |
| Notes | LOCKABLE ON-OFF | | |
| GLOW WIRE | GW 650°C | | |
| Protection degree IK | IK09 | | |