

690.4200-303

DISTRIBUTION ASSEMBLY

5 NR IP44



Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|--------------------------------|-----------------------|-----------------------------------|---|
| Protection degree | Splash proof | EN 61439-3 (2012-04) | [European Standard] Low-voltage switchgear and controlgear assemblies - Part 3: Distribution boards intended to be operated by ordinary persons (DBO) |
| Mounting version | PORTABLE | | |
| Type of product | DISTRIBUTION ASSEMBLY | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Commercial series | IMPACT Series | DIRECTIVE EMC 2014/30/UE | [European Directives] Electromagnetic Compatibility Directive |
| Synthetical description | DISTRIBUTION ASSEMBLY | | |
| Material | RUBBER | | |
| Protection degree IP | IP44 | | |
| Protection degree IK | IK09 | | |
| Inlet supply unit | Plug | | |
| No. of available outlets | 5 NR | | |
| No. p.m. socket 2P+E 16A P40 | 3 NR | | |
| No. of sockets 2P+E 16A | 2 NR | | |
| In disp. ing/tipo apparecchio | RCD 2P 25A 0,03A | | |
| In disp. ing/tipo apparecchio | MCB 2P 16A | | |
| Max power | 3 KW | | |
| No. switch disconnecter 1P 16A | 5 NR | | |