



204.CA22B-T2T2EV

COLUMNA CA 2 TOMAS CON BLOQUEO

Type 2 1P+N+T 32A 230V~ 7,4kW Type 2
3P+N+T 32A 400V~ 22kW 63A 400V 3P+N+T
IP54 IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	COLUMNA CA 2 TOMAS CON BLOQUEO	IEC 61851-1 (2010)	[International Standard] Electric vehicle conductive charging system - Part 1: General requirements
Serie comercial	Serie LIBERA	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Descripción sintética	COLUMNA CA 2 TOMAS CON BLOQUEO		
Material	METAL BARNIZADO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 2 1P+N+T 32A 230V~ 7,4kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
EV standard	Type 2 3P+N+T 32A 400V~ 22kW		
Intensidad nominal	63A		
Tensión nominal	400V		
Frecuencia nominal	50/60Hz		
Polos	3P+N+T		
Grado de protección IP	IP54		
Temperatura de ejercicio	-25°C/+40°C		
Grado de protección IK	IK10		
Color	GRIS		
Tipo de instalación	TORRETA		
Dimensiones	385x1510x263mm		