



204.CA23B-T2T2EV

COLUMNA CA 2 TOMAS CON BLOQUEO

Type 2 3P+N+T 32A 400V~ 22kW 63A 400V
3P+N+T IP54 IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	COLUMNA CA 2 TOMAS CON BLOQUEO	IEC 61851-1 (2010)	[International Standard] Electric vehicle conductive charging system - Part 1: General requirements
Serie comercial	Serie LIBERA	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Descripción	COLUMNA CA 2 TOMAS CON BLOQUEO		
Material	METAL BARNIZADO		
EV standard	Type 2 3P+N+T 32A 400V~ 22kW	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	63A	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Tensión nominal	400V		
Frecuencia nominal	50/60Hz		
Polos	3P+N+T		
Grado de protección IP	IP54		
Temperatura de ejercicio	-25°C/+40°C		
Grado de protección IK	IK10		
Color	GRIS		
Tipo de instalación	TORRETA		
Dimensiones	385x1510x263mm		
Certificaciones	EV READY 1.4		