



219.3235

CLAVIJA AÉREA

32A 3P+N+T 9h 208-250V 50Hz 60Hz II 2GD
Low temperature [-50°C]

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie OPTIMA-EX[GD]	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipo de producto	CLAVIJA AÉREA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción sintética	CLAVIJA AÉREA		
Tipo de instalación	PORTÁTIL		
Intensidad nominal	32A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Polos	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Posición de hora	9h		
Tensión nominal (range)	200-250V	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensión nominal	208-250V		
Frecuencia nominal	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Frecuencia nominal	50Hz		
Color	AZUL	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Material	TERMOPLÁSTICO	IEC 60079-0 (2011)	[International Standard] Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements.
Grado de protección	Splash proof	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Grado de protección IP	IP66		
Tipos de salidas disponibles	RECTA	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Salida del cable	PRENSAESTOPAS	EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
Grupo y categorías EX	II 2GD	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1:

Temperatura ambiente Ta min	-50 °C	EN 60079-7 (2015)	Flameproof enclosures 'd' [European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Temperatura ambiente Ta max	60 °C	IEC 60079-1 (2014)	[International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Opciones	Low temperature [-50°C]	IEC 60079-7 (2015) DIRECTIVE ATEX 2014/34/UE	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e". [European Directives] Atmosphere Explosive