



219.63364.RU

CLAVIJA AÉREA

63A 3P+T 3h 380V 50Hz / 440V 60Hz 50Hz
60Hz II 2GD EAC [Eurasian Conformity]

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie OPTIMA-EX[GD]	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipo de producto	CLAVIJA AÉREA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción sintética	CLAVIJA AÉREA		
Tipo de instalación	PORTÁTIL		
Intensidad nominal	63A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Polos	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Posición de hora	3h		
Tensión nominal (range)	250-400V	EN 60079-7 (2007)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Tensión nominal	380V 50Hz / 440V 60Hz		
Frecuencia nominal	60Hz	IEC 60079-7 (2006-07)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Frecuencia nominal	50Hz	EN 60079-1 (2007)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures "d"
Color	ROJO		
Material	TERMOPLÁSTICO	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Grado de protección	Splash proof	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Grado de protección IP	IP66		
Tipos de salidas disponibles	RECTA	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Salida del cable	PRENSAESTOPAS	IEC 60079-0 (2011)	[International Standard] Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements.
Grupo y categorías EX	II 2GD	IEC 60079-1 (2007-)	[International Standard] Explosive

Temperatura ambiente Ta min	-35 °C	04)	atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Temperatura ambiente Ta max	60 °C	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Opciones	EAC [Eurasian Conformity]	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
		EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
		DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive