


245.M6396

BASE CONNECTORA MURAL

63A 3P+T 6h 380-415V 50Hz 60Hz Bornes con tornillo



Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie OPTIMA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipo de producto	BASE CONNECTORA MURAL	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción	BASE CONNECTORA MURAL		
Tipo de instalación	MURAL	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	63A		
Polos	3P+T		
Posición de hora	6h		
Tensión nominal (range)	250-400V		
Tensión nominal	380-415V		
Frecuencia nominal	50Hz		
Frecuencia nominal	60Hz		
Color	ROJO		
Material	TERMOPLÁSTICO		
Grado de protección	Watertight		
Grado de protección IP	IP66/IP67/IP69		
Grado de protección IK	IK08		
Tipos de salidas disponibles	INCLINADA		
Bornes	Bornes con tornillo		

Material de los contactos	CuZn (latón)
Tratamiento superficial cont.	Con revestimiento de níquel
Salida del cable	M32X1,5