



316.1643

PROLONGADOR

16A 2P+T 6h 200-250V 50Hz 60Hz Bornes con tornillo

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|------------------------------|---------------------|-----------------------------------|---|
| Tipo de producto | PROLONGADOR | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie comercial | Serie EUREKA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción | PROLONGADOR | | |
| Tipo de instalación | PORTÁTIL | | |
| Intensidad nominal | 16A | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Polos | 2P+T | | |
| Posición de hora | 6h | | |
| Tensión nominal (range) | 200-250V | | |
| Tensión nominal | 200-250V | | |
| Frecuencia nominal | 60Hz | | |
| Frecuencia nominal | 50Hz | | |
| Color | AZUL | | |
| Material | TERMOPLÁSTICO | | |
| Grado de protección | Watertight | | |
| Grado de protección IP | IP66/IP67 | | |
| Grado de protección IK | IK07 | | |
| Tipos de salidas disponibles | RECTA | | |
| Bornes | Bornes con tornillo | | |

| | |
|---------------------------|---------------|
| Material de los contactos | CuZn (latón) |
| Salida del cable | PRENSAESTOPAS |