



# 407.3274

## BASE CON BLOQUEO

32A 3P+T 9h 200-250V 50Hz 60Hz  
103X230MM Bornes con tornillo Con  
enclavamiento mecánico

Product Approvals

| TECHDATA                  |                     | STANDARDS AND LAWS                |   |
|---------------------------|---------------------|-----------------------------------|---|
| Serie comercial           | PRX                 | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Tipo de producto          | BASE CON BLOQUEO    | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción               | BASE CON BLOQUEO    |                                   |   |
| Tipo de instalación       | EMPOTRABLE          |                                   |   |
| Intensidad nominal        | 32A                 | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Polos                     | 3P+T                | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Posición de hora          | 9h                  |                                   |   |
| Tensión nominal (range)   | 200-250V            | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Tensión nominal           | 200-250V            |                                   |   |
| Frecuencia nominal        | 60Hz                | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Frecuencia nominal        | 50Hz                | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Color                     | AZUL                |                                   |   |
| Material                  | TERMOPLÁSTICO       |                                   |   |
| Grado de protección       | Watertight          | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Grado de protección IP    | IP66/IP67/IP69      |                                   |   |
| Grado de protección IK    | IK10                | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Bornes                    | Bornes con tornillo | DIRECTIVE RoHS 2011/65/EU         | [European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment  |
| Material de los contactos | CuZn (latón)        |                                   |   |

|                   |                            |
|-------------------|----------------------------|
| Brida de fijación | 103X230MM                  |
| Opciones          | Con enclavamiento mecánico |
| Notas             | SIN PORTAFUSIBLES          |
| Candado           | ø5mm                       |