



# 407.63861

## BASE CON BLOQUEO

63A 3P+T 10h >50V 100-300Hz 136X275MM

Bornes con tornillo Con enclavamiento mecánico

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	PRX	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipo de producto	BASE CON BLOQUEO	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción	BASE CON BLOQUEO		
Tipo de instalación	EMPOTRABLE		
Intensidad nominal	63A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Polos	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Posición de hora	10h		
Tensión nominal (range)	50-200V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensión nominal	>50V		
Frecuencia nominal	100-300Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Color	VERDE	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Material	TERMOPLÁSTICO		
Grado de protección	Watertight		
Grado de protección IP	IP66/IP67/IP69	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado de protección IK	IK09		
Bornes	Bornes con tornillo	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Material de los contactos	CuZn (latón)	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Brida de fijación	136X275MM		

Opciones	Con enclavamiento mecánico
Notas	SIN PORTAFUSIBLES
Candado	ø5mm