



# 418.125672

## BASE EMPOTRABLE

125A 3P+N+T 2h >50V >300-500Hz  
114X114MM Bornes conexión brida tornillo

Product Approvals

| TECHDATA                     |                                | STANDARDS AND LAWS                |   |
|------------------------------|--------------------------------|-----------------------------------|---|
| Serie comercial              | Serie OPTIMA                   | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Tipo de producto             | BASE EMPOTRABLE                | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción                  | BASE EMPOTRABLE                |                                   |   |
| Tipo de instalación          | EMPOTRABLE                     |                                   |   |
| Intensidad nominal           | 125A                           | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Polos                        | 3P+N+T                         | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Posición de hora             | 2h                             |                                   |   |
| Tensión nominal (range)      | 50-200V                        | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Tensión nominal              | >50V                           |                                   |   |
| Frecuencia nominal           | >300-500Hz                     | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Color                        | VERDE                          |                                   |   |
| Material                     | TERMOPLÁSTICO                  | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Grado de protección          | Watertight                     |                                   |   |
| Grado de protección IP       | IP66/IP67/IP69                 |                                   |   |
| Grado de protección IK       | IK08                           |                                   |   |
| Tipos de salidas disponibles | INCLINADA                      |                                   |   |
| Bornes                       | Bornes conexión brida tornillo |                                   |   |
| Material de los contactos    | CuZn (latón)                   |                                   |   |

Brida de fijación

114X114MM