

500.M16865

BASE ENCLAV. MEC.

16A 3P+T 11h 440-460V 60Hz
136X125MM_PAR Bornes con tornillo Con
enclavamiento mecánico



Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	BASE ENCLAV. MEC.	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie comercial	Serie OMNIA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción	BASE ENCLAV. MEC.		
Tipo de instalación	MURAL		
Intensidad nominal	16A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Polos	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Posición de hora	11h		
Tensión nominal (range)	400V-up	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensión nominal	440-460V		
Frecuencia nominal	60Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Color	ROJO	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Material	TERMOPLÁSTICO		
Grado de protección	Splash proof		
Grado de protección IP	IP44	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado de protección IK	IK08		
Bornes	Bornes con tornillo	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Material de los contactos	CuZn (latón)		
Brida de fijación	136X125MM_PAR		

Opciones	Con enclavamiento mecánico
Notas	SIN PORTAFUSIBLES