

# Product Technical Sheet

21 feb 2022 18:27



## TECHDATA

Tipo de producto

BASE ENCLAV. MEC.

## STANDARDS AND LAWS

EN 60309-1 (1999) [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part

Serie comercial	Serie OMNIA	EN 60309-2 (1999)	1: General requirements
Descripción	BASE ENCLAV. MEC.		[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Tipo de instalación	MURAL		
Intensidad nominal	32A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Polos	2P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Posición de hora	6h		
Tensión nominal (range)	200-250V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensión nominal	200-250V		
Frecuencia nominal	60Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Frecuencia nominal	50Hz		
Color	AZUL	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Material	TERMOPLÁSTICO		
Grado de protección	Splash proof	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado de protección IP	IP44		
Grado de protección IK	IK08	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Bornes	Bornes con tornillo		
Material de los contactos	CuZn (latón)		
Brida de fijación	136X125MM_PAR		
Opciones	Con enclavamiento mecánico		
Notas	SIN PORTAFUSIBLES		