



504.3278-A

BASE ENCLAV. MEC.

32A 2P+T 9h 380-415V 50Hz 60Hz II 2GD
130X260MM_PAR Bornes con tornillo Con
enclavamiento mecánico Low temperature [-50°
C]

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	BASE ENCLAV. MEC.	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie comercial	Serie ADVANCE-GRP[GD]	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción	BASE ENCLAV. MEC.		
Tipo de instalación	MURAL		
Intensidad nominal	32A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Polos	2P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Posición de hora	9h		
Tensión nominal (range)	250-400V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensión nominal	380-415V		
Frecuencia nominal	50Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Frecuencia nominal	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Color	ROJO		
Material	GRP Glass Reinforced Polyester		
Grado de protección	Splash proof	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado de protección IP	IP66	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Grado de protección IK	IK10		
Bornes	Bornes con tornillo	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Material de los contactos	CuZn (latón)	EN 60079-7 (2015)	[European Standard] Explosive

Brida de fijación	130X260MM_PAR		atmospheres. Equipment protection by increased safety "e"
Salida del cable	1xM32	EN 60079-7 (2018)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Temperatura de ejercicio	-40°C/+60°C	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
Prueba del hilo incandescente	GW 960°C	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Autoextinguible UL94	V0		
Grupo y categorías EX	II 2GD		
Temperatura ambiente Ta min	-50 °C		
Temperatura ambiente Ta max	60 °C		
Opciones	Con enclavamiento mecánico		
Opciones	Low temperature [-50°C]		
Candado	ø5mm		