



## 504.32865

### BASE ENCLAV. MEC.

32A 3P+T 11h 440-460V 60Hz II 2GD  
130X260MM\_PAR Bornes con tornillo Con  
enclavamiento mecánico

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	BASE ENCLAV. MEC.	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie comercial	Serie ADVANCE-GRP[GD]	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción	BASE ENCLAV. MEC.	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipo de instalación	MURAL	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Intensidad nominal	32A	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Polos	3P+T	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Posición de hora	11h	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Tensión nominal (range)	400V-up	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Tensión nominal	440-460V	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Frecuencia nominal	60Hz	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Color	ROJO	EN 60079-7 (2015)	[European Standard] Explosive
Material	GRP Glass Reinforced Polyester		
Grado de protección	Splash proof		
Grado de protección IP	IP66		
Grado de protección IK	IK10		
Bornes	Bornes con tornillo		
Material de los contactos	CuZn (latón)		
Brida de fijación	130X260MM_PAR		

Salida del cable	1xM32		atmospheres. Equipment protection by increased safety "e"
Temperatura de ejercicio	-40°C/+60°C	EN 60079-7 (2018)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Prueba del hilo incandescente	GW 960°C	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
Autoextinguible UL94	V0	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Grupo y categorías EX	II 2GD		
Temperatura ambiente Ta min	-35 °C		
Temperatura ambiente Ta max	60 °C		
Opciones	Con enclavamiento mecánico		
Candado	ø5mm		