



## 504.6379.RU

### BASE ENCLAV. MEC.

63A 3P+N+T 4h 100-130V 50Hz 60Hz II 2GD  
130X260MM\_PAR Con enclavamiento  
mecánico EAC [Eurasian Conformity]

Product Approvals

| TECHDATA                |                                | STANDARDS AND LAWS    |   |
|-------------------------|--------------------------------|-----------------------|---|
| Serie comercial         | Serie ADVANCE-GRP[GD]          | EN 60309-1 (1999)     | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Tipo de producto        | BASE ENCLAV. MEC.              | EN 60309-2 (1999)     | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción sintética   | BASE ENCLAV. MEC.              |                       |   |
| Tipo de instalación     | MURAL                          |                       |   |
| Intensidad nominal      | 63A                            | EN 60309-1/A1 (2007)  | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Polos                   | 3P+N+T                         | EN 60309-2/A1 (2007)  | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Posición de hora        | 4h                             |                       |   |
| Tensión nominal (range) | 50-200V                        | EN 60079-7 (2007)     | [European Standard] Explosive atmospheres. Equipment protection by increased safety "e"   |
| Tensión nominal         | 100-130V                       |                       |   |
| Frecuencia nominal      | 50Hz                           | EN 60309-4 (2007)     | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Frecuencia nominal      | 60Hz                           |                       |   |
| Color                   | AMARILLO                       | IEC 60079-7 (2006-07) | [International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".  |
| Material                | GRP Glass Reinforced Polyester | EN 60079-1 (2007)     | [European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures "d"  |
| Grado de protección     | Splash proof                   | EN 60309-1/A2 (2012)  | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Grado de protección IP  | IP66                           |                       |   |
| Brida de Fijación       | 130X260MM_PAR                  | EN 60309-2/A2 (2012)  | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Salida del cable        | 1xM40                          |                       |   |
| Grupo y categorías EX   | II 2GD                         | IEC 60309-1 (2012)    | [International Standard] Plugs, socket-outlets and couplers for industrial  |

|                             |                            |                           |  |
|-----------------------------|----------------------------|---------------------------|--|
| Temperatura ambiente Ta min | -35 °C                     | IEC 60309-2 (2012)        | purposes. - Part 1: General requirements<br>[International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories |
| Temperatura ambiente Ta max | 60 °C                      |                           |  |
| Opciones                    | EAC [Eurasian Conformity]  | EN 60309-4/A1 (2012)      | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock  |
| Opciones                    | Con enclavamiento mecánico |                           |  |
| Candado                     | ø6,3mm                     | IEC 60309-4 (2012)        | [International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 4: Switched socket-outlets and connectors with or without interlock  |
|                             |                            | EN 60079-0 (2012)         | [European Standard] Explosive atmospheres. General requirements.   |
|                             |                            | IEC 60079-0 (2011)        | [International Standard] Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements.  |
|                             |                            | IEC 60079-1 (2007-04)     | [International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".  |
|                             |                            | EN 60079-31 (2014)        | [European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"   |
|                             |                            | IEC 60079-31 (2013)       | [International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"  |
|                             |                            | DIRECTIVE ATEX 2014/34/UE | [European Directives] Atmosphere Explosive   |