



# 508.32838

## BASE CON BLOQUEO

32A 2P+T 8h >250V Corr. continua Bornes con tornillo Con enclavamiento mecánico

Product Approvals

| TECHDATA                  |                            | STANDARDS AND LAWS                |   |
|---------------------------|----------------------------|-----------------------------------|---|
| Tipo de producto          | BASE CON BLOQUEO           | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Serie comercial           | PRX                        | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción               | BASE CON BLOQUEO           |                                   |   |
| Tipo de instalación       | MURAL                      |                                   |   |
| Intensidad nominal        | 32A                        | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Polos                     | 2P+T                       | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Posición de hora          | 8h                         |                                   |   |
| Tensión nominal (range)   | 250V-up                    | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Tensión nominal           | >250V                      |                                   |   |
| Frecuencia nominal        | Corr. continua             | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Color                     | GRIS                       | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Material                  | TERMOPLÁSTICO              |                                   |   |
| Grado de protección       | Watertight                 |                                   |   |
| Grado de protección IP    | IP66/IP67/IP69             | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Grado de protección IK    | IK10                       |                                   |   |
| Bornes                    | Bornes con tornillo        | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Material de los contactos | CuZn (latón)               | DIRECTIVE RoHS 2011/65/EU         | [European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment  |
| Opciones                  | Con enclavamiento mecánico |                                   |   |

|                 |                   |
|-----------------|-------------------|
| Notas           | CON PORTAFUSIBLES |
| Tipo de fusible | gG 10,3x38mm      |
| Candado         | ø5mm              |