

Product Technical Sheet

21 feb 2022 17:57



517.M3250 BASE MURAL

32A 2P+T 4h 100-130V 50Hz 60Hz Bornes con tornillo

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|------------------------------|---------------------|-----------------------------------|---|
| Tipo de producto | BASE MURAL | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie comercial | Serie OPTIMA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción | BASE MURAL | | |
| Tipo de instalación | MURAL | | |
| Intensidad nominal | 32A | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Polos | 2P+T | | |
| Posición de hora | 4h | | |
| Tensión nominal (range) | 50-200V | | |
| Tensión nominal | 100-130V | | |
| Frecuencia nominal | 60Hz | | |
| Frecuencia nominal | 50Hz | | |
| Color | AMARILLO | | |
| Material | TERMOPLÁSTICO | | |
| Grado de protección | Watertight | | |
| Grado de protección IP | IP66/IP67/IP69 | | |
| Grado de protección IK | IK08 | | |
| Tipos de salidas disponibles | INCLINADA | | |
| Bornes | Bornes con tornillo | | |

| | |
|---------------------------|--------------|
| Material de los contactos | CuZn (latón) |
| Salida del cable | M25X1,5 |