



# 527.M32561

## BASE MURAL

32A 3P+T 10h >50V 100-300Hz Bornes con tornillo

Product Approvals

| TECHDATA                     |                     | STANDARDS AND LAWS                |   |
|------------------------------|---------------------|-----------------------------------|---|
| Tipo de producto             | BASE MURAL          | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Serie comercial              | Serie OPTIMA        | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción                  | BASE MURAL          |                                   |   |
| Tipo de instalación          | MURAL               |                                   |   |
| Intensidad nominal           | 32A                 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Polos                        | 3P+T                |                                   |   |
| Posición de hora             | 10h                 |                                   |   |
| Tensión nominal (range)      | 50-200V             |                                   |   |
| Tensión nominal              | >50V                |                                   |   |
| Frecuencia nominal           | 100-300Hz           |                                   |   |
| Color                        | VERDE               |                                   |   |
| Material                     | TERMOPLÁSTICO       |                                   |   |
| Grado de protección          | Watertight          |                                   |   |
| Grado de protección IP       | IP66/IP67/IP69      |                                   |   |
| Grado de protección IK       | IK08                |                                   |   |
| Tipos de salidas disponibles | RECTA               |                                   |   |
| Bornes                       | Bornes con tornillo |                                   |   |
| Material de los contactos    | CuZn (latón)        |                                   |   |

Salida del cable

M25X1,5