



579.EX40-107

CUADRO DE DISTRIBUCIÓN

IP66 32A II 3D

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Grado de protección	Splash proof	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Intensidad nominal	32A	EN 61439-3 (2012-04)	[European Standard] Low-voltage switchgear and controlgear assemblies - Part 3: Distribution boards intended to be operated by ordinary persons (DBO)
Tipo de instalación	MURAL	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Tipo de producto	CUADRO DE DISTRIBUCIÓN	EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
Serie comercial	Sistema ADVANCE-GRP	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Descripción	CUADRO DE DISTRIBUCIÓN	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Material	GRP Glass Reinforced Polyester		
Grado de protección IP	IP66		
Prueba del hilo incandescente	GW 960°C		
Autoextinguible UL94	V0		
Grupo y categorías EX	II 3D		
Temperatura ambiente Ta min	-25 °C		
Temperatura ambiente Ta max	60 °C		