



590.FEM2006.U

INTERRUPTOR DE MANIOBRA

20A 6P IP65 253x217x93mm EMERGENCIA
AMARILLO/ROJO FIRE RATED 1xNA+1xNC
IK10

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|------------------------|------------------------------|-----------------------------------|---|
| Serie comercial | Serie ISOLATORS-FR | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Tipo de producto | INTERRUPTOR DE MANIOBRA | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Descripción sintética | INTERRUPTOR DE MANIOBRA | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | ALUMINIO VACIADIZO A PRESIÓN | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Grado de protección IP | IP65 | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Tipo | EMERGENCIA | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Color | AMARILLO/ROJO | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Intensidad nominal | 20A | | |
| Polos | 6P | | |
| Dimensiones | 253x217x93mm | | |
| Notas | FIRE RATED | | |
| Fire rated class | F400 (120min) | | |
| Notas | 1xNA+1xNC | | |
| Grado de protección IK | IK10 | | |