



590.FGE2005.U

INTERRUPTOR DE MANIOBRA

20A 3P+N IP65 192x168x80mm GENERAL
GRIS/NEGRO FIRE RATED 1xNA+1xNC IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie ISOLATORS-FR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción sintética	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ALUMINIO VACIADIZO A PRESIÓN	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado de protección IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Color	GRIS/NEGRO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	20A		
Polos	3P+N		
Dimensiones	192x168x80mm		
Notas	FIRE RATED		
Fire rated class	F400 (120min)		
Notas	1xNA+1xNC		
Grado de protección IK	IK10		