



590.FGE3202

INTERRUPTOR DE MANIOBRA

32A 2P IP65 192x168x80mm GENERAL GRIS /NEGRO FIRE RATED IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Serie comercial	Serie ISOLATORS-FR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción sintética	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ALUMINIO VACIADIZO A PRESIÓN	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado de protección IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Color	GRIS/NEGRO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	32A		
Polos	2P		
Dimensiones	192x168x80mm		
Notas	FIRE RATED		
Fire rated class	F400 (120min)		
Grado de protección IK	IK10		