



# 590.HEM2508

## INTERRUPTOR DE MANIOBRA

25A 8P IP66 150x210x107mm Y3 IK10  
EMERGENCIA AMARILLO/ROJO

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Serie comercial	Serie ISOLATORS-AL	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ALUMINIO VACIADIZO A PRESIÓN	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado de protección IP	IP66	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	EMERGENCIA	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Color	AMARILLO/ROJO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	25A		
Polos	8P		
Tamaño interr.	Y3		
Tensión nominal	690V		
Dimensiones	150x210x107mm		
Grado de protección IK	IK10		