



590.KEMD20005

INTERRUPTOR DE MANIOBRA

200A 3P+N IP65 DIN-NH 400x600x200mm KF3
IK10 EMERGENCIA AMARILLO/ROJO FUSE:
DIN-NH

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie ISOLATORS-HR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	METAL	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado de protección IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	EMERGENCIA	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Color	AMARILLO/ROJO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	200A		
Polos	3P+N		
Tamaño interr.	KF3		
Tipo de fusible	DIN-NH		
Tensión nominal	690V		
Dimensiones	400x600x200mm		
Notas	FUSE: DIN-NH		
Grado de protección IK	IK10		