



# 590.YU21251

## INTERRUPTOR DE MANIOBRA

### 125A 4 POLOS Y4 GENERAL

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie COMMAND[UL]	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	TERMOPLÁSTICO	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipo	GENERAL	UL 60947-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 1: General rules
Intensidad nominal	125A	UL 60947-4-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 4-1: Contactors and Motor-Starters - Electromechanical Contactors and Motor-Starters
Polos	4 POLOS	CSA C22.2 No. 60947-1-13	[Canadian Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tamaño interr.	Y4	CSA C22.2 No. 60947-4-1-14	[Canadian Standard] Low-voltage switchgear and controlgear - Part 4-1: Contactors and motor-starters - Electromechanical contactors and motor-starters
Tensión nominal	690V	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
		EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
		DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive

/UE