



592.R001-02-B

INTERRUPTOR BIPOLAR

INTERRUPTOR BIPOLAR 16AX 2xM20 II 2GD
-50 °C 60 °C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	INTERRUPTOR BIPOLAR	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Serie comercial	Serie ROCKER-EX[GD]	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Descripción	INTERRUPTOR BIPOLAR	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Tipo de instalación	MURAL	EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
Grado de protección	Splash proof	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Grado de protección IP	IP66	EN 60079-7 (2015)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Material	TERMOPLÁSTICO	IEC 60079-1 (2014)	[International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Intensidad nominal	16AX	EN 60669-1 (2018)	[European Standard] Switches for household and similar fixed-electrical installations. Part 1: General requirements
Tensión nominal	250V	IEC 60669-1 (2017)	[International Standard] Switches for household and similar fixed-electrical installations. - Part 1: General requirements.
Notas	2xM20	IEC 60079-0 (2017)	[International Standard] Explosive atmospheres - Part 0: Equipment - General requirements
Grupo y categorías EX	II 2GD	IEC 60079-7 (2017)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Temperatura ambiente Ta min	-50 °C	EN 60079-7 (2018)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Temperatura ambiente Ta max	60 °C	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive