



## 645.B6S03

### CAJA MURAL

100x160x90mm IP66 GRIS ACERO INOXIDABLE [AISI316L] Silicon

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	CAJA MURAL	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Serie comercial	Serie ZENITH-S	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Descripción	CAJA MURAL	EN 60079-7 (2015)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Grado de protección	Splash proof	IEC 60079-7 (2015)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Grado de protección IP	IP66	IEC 60079-0 (2017)	[International Standard] Explosive atmospheres - Part 0: Equipment - General requirements
Material	ACERO INOXIDABLE [AISI316L]	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
Grado de protección IK	IK10	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Junta	Silicon		
Color	GRIS		
Dimensiones	100x160x90mm		
Grupo y categorías EX	II 2GD		
Modo de protección gas	Ex eb IIC Gb		
Modo de protección Polvo	Ex tb IIIC Db IP66		
Temperatura ambiente Ta min	-50 °C		
Temperatura ambiente Ta max	95 °C		