

# 645.C4S050

## CAJA

380x380x210mm IP66 GRIS ACERO  
INOXIDABLE [AISI304L] Silicon



Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie ZENITH-S	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Tipo de producto	CAJA	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Descripción	CAJA	EN 60079-7 (2015)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Grado de protección	Splash proof	IEC 60079-7 (2015)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Grado de protección IP	IP66	IEC 60079-0 (2017)	[International Standard] Explosive atmospheres - Part 0: Equipment - General requirements
Material	ACERO INOXIDABLE [AISI304L]	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
Grado de protección IK	IK10	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Junta	Silicon		
Color	GRIS		
Dimensiones	380x380x210mm		
Grupo y categorías EX	II 2GD		
Modo de protección gas	Ex eb IIC Gb		
Modo de protección Polvo	Ex tb IIIC Db IP66		
Temperatura ambiente Ta min	-50 °C		
Temperatura ambiente Ta max	95 °C		