



657.H6121-080

CUADRO DE OBRA

6 NR IP65 475x520x380mm

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Grado de protección	Splash proof	EN 61439-4 (2013-03)	[European Standard] Low-voltage switchgear and controlgear assemblies - Part 4: Particular requirements for assemblies for construction sites (ACS)
Tipo de instalación	MURAL		
Serie comercial	MBX3	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Tipo de producto	CUADRO DE OBRA		
Descripción	CUADRO DE OBRA	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Material	TERMOPLÁSTICO		
Dimensiones	475x520x380mm		
Grado de protección IP	IP65		
Grado de protección IK	IK08		
Unidad de alimentación	Aliment. de regletas		
N.º de salidas disponibles	6 NR		
N.bases 2P+T 16A	3 NR		
N.bases 3P+T 16A	2 NR		
Tipo de aparato	Interrupt.diferen.4P 63A 0,03 A		
Tipo de aparato	Interrupt. magnetot. 4P 63A		
Potencia máx	1X		
N.Int.magnetotermico 1P+N 16A	1 NR		
N.Int.magnetotermico 3P 16A	1 NR		

