



899.AS5AR318

BASE EMPOTRABLE

420A 3P+T 1.000V Bornes a presión

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------------|------------------------------|-----------------------------------|---|
| Tipo de producto | BASE EMPOTRABLE | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie comercial | Serie OPTIMA-METAL | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción | BASE EMPOTRABLE | | |
| Tipo de instalación | EMPOTRABLE | | |
| Intensidad nominal | 420A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Polos | 3P+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Tensión nominal (range) | 400V-up | | |
| Tensión nominal | 1.000V | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Material | ALUMINIO VACIADIZO A PRESIÓN | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Grado de protección | Watertight | | |
| Grado de protección IP | IP67 | | |
| Grado de protección IK | IK10 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Bornes | Bornes a presión | | |
| Material de los contactos | CuZn (latón) | | |
| Tratamiento superficial cont. | Con revestimiento de plata | | |
| Sección del cable | 185 mm ² | | |